

BLACK SABRE PLATE MOUNTED SICKLE FANS PERFORMANCE GUIDE

2 POLE

m³/s at Pa

Dia.	Motor	Stock		IP												Motor kW	S.C. Amps	F.L.C. Amps	dBA @ 3m		
		Ref. No.	r.p.m.	Rating	0	25	50	75	100	125	150	175	200	225	250					300	350
250	1 phase	BSP250-12	2650	IP54	0.45	0.42	0.38	0.34	0.30	0.23	0.135	0.086	0.046					0.12	2.20	0.55	54

4 POLE

250	1 phase	BSP250-14	1450	IP54	0.220	0.151	0.065	0.020										0.04	0.84	0.21	41
315	1 phase	BSP315-14	1400	IP54	0.581	0.532	0.463	0.381	0.222	0.179	0.123	0.057						0.12	2.12	0.53	46
	3 phase	BSP315-34	1420	IP54	0.584	0.535	0.465	0.382	0.223	0.180	0.123	0.057						0.13	2.76	0.46	
355	1 phase	BSP355-14	1400	IP54	0.784	0.721	0.638	0.554	0.453	0.258	0.198	0.118						0.12	2.20	0.55	48
	3 phase	BSP355-34	1400	IP54	0.835	0.770	0.682	0.592	0.488	0.282	0.226	0.175	0.083					0.15	2.52	0.42	
400	1 phase	BSP400-14	1360	IP54	1.555	1.458	1.291	1.062	0.583	0.465	0.363							0.32	6.40	1.60	51
	3 phase	BSP400-34	1380	IP54	1.555	1.458	1.291	1.062	0.583	0.465	0.363							0.36	4.40	1.10	
450	1 phase	BSP450-14	1280	IP54	1.902	1.885	1.720	1.602	1.495	1.280	0.860	0.742	0.640	0.508	0.383	0.114		0.63	11.20	2.80	54
	3 phase	BSP450-34*	1340	IP54	1.976	1.891	1.781	1.667	1.514	1.326	0.890	0.748	0.642	0.508	0.382	0.113		0.59	7.80	1.30	
500	1 phase	BSP500-14	1350	IP54	2.667	2.576	2.463	2.301	2.140	1.945	1.682	1.271	1.087	0.915	0.766	0.469	0.229	0.85	15.20	3.80	59
	3 phase	BSP500-34*	1370	IP54	2.708	2.615	2.500	2.336	2.173	1.975	1.708	1.290	1.104	0.929	0.778	0.476	0.232	0.97	11.40	1.90	
560	1 phase	BSP560-14	1300	IP54	3.472	3.337	3.179	3.021	2.840	2.615	2.344	2.029	1.616	1.374	1.172	0.744	0.383	1.30	24.00	6.00	65
	3 phase	BSP560-34*	1340	IP54	3.579	3.440	3.277	3.114	2.928	2.696	2.417	2.092	1.666	1.417	1.208	0.767	0.395	1.40	15.00	2.50	
630	1 phase	BSP630-14	1325	IP54	3.982	3.843	3.657	3.449	3.218	2.963	2.699	2.440	2.176	1.782	1.551	1.180	0.925	1.30	22.80	5.70	68
	3 phase	BSP630-34*	1330	IP54	3.998	3.858	3.672	3.463	3.231	2.975	2.710	2.450	2.185	1.789	1.557	1.185	0.929	1.40	15.00	2.50	

6 POLE

450	1 phase	BSP450-16	880	IP54	1.260	1.095	0.901	0.690	0.416	0.250								0.21	4.00	1.00	47
	3 phase	BSP450-36*	1050	IP54	1.570	1.480	1.374	1.261	1.114	0.724	0.553	0.388	0.219						0.23	3.42	0.57
500	1 phase	BSP500-16	870	IP54	1.722	1.527	1.236	0.694	0.486	0.280								0.31	5.20	1.30	51
	3 phase	BSP500-36*	900	IP54	2.336	2.196	2.045	1.894	1.720	1.487	1.092	0.813	0.569	0.348	0.127				0.27	3.72	0.62
560	1 phase	BSP560-16	820	IP54	2.311	2.070	1.777	1.083	0.695	0.362	0.202							0.41	7.20	1.80	57
	3 phase	BSP560-36*	860	IP54	3.091	2.928	2.777	2.580	2.370	2.138	1.859	1.371	1.022	0.743	0.464				0.45	5.40	0.90
630	1 phase	BSP630-16	830	IP54	3.055	2.820	2.361	1.666	1.095	0.580	0.325							0.70	12.40	3.10	61
	3 phase	BSP630-36*	880	IP54	3.486	3.277	3.068	2.812	2.556	2.324	2.045	1.720	1.255	0.813	0.464				0.74	9.00	1.50
710	1 phase	BSP710-16	860	IP54	4.311	4.013	3.652	3.269	2.840	2.006	1.616	1.330	1.037	0.766	0.518			0.90	16.00	4.00	63
	3 phase	BSP710-36*	920	IP54	4.444	4.137	3.765	3.370	2.928	2.068	1.666	1.371	1.069	0.790	0.534			1.00	15.60	2.60	

8 POLE

710	3 phase	BSP710-38*	670	IP54	3.280	2.887	2.071	1.110	0.306	0.291								0.46	7.80	1.30	53
-----	---------	-------------------	-----	------	-------	-------	-------	-------	--------------	--------------	--	--	--	--	--	--	--	------	------	------	----

S.C. = STARTING CURRENT
F.L.C. = FULL LOAD CURRENT

NOTE: All * models are supplied with 2 speed connection motors as standard. (Sizes 450-630 dia. are 4/6 pole, 710 are 6/8 pole).
DELTA Δ (HIGH SPEED)
STAR * (LOW SPEED)

ONLY SELECT THE FANS TYPED IN RED WHEN CONFIDENT OF YOUR SYSTEM RESISTANCE DATA.